



Low VF Bridge Rectifiers



Features

- Glass Passivated Chip Junction
- Low IRRM
- Low VF
- High VRRM

Benefits

- Case: GBU
- Terminals: Solderable Per MIL-STD-750
- Reduced power loss and switching transistor
- Reduced snubbing

Maximum Ratings and Electrical characteristics

Ratings at 25 ºC ambient temperature unless otherwise specified.

Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	GBU806L	Units
Maximum Repetitive Peak Reverse Voltage	VRRM	600	V
Maximum RMS voltage	VRMS	420	V
Maximum DC Blocking Voltage	VDC	600	V
Average Rectified Output Current	Io	8.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	IFSM	120	A
Maximum Forward Voltage at 4.0 A	VF	0.95	V
Maximum DC Reverse Current @TA=25 ºC at Rated DC Blocking Voltage @TA=125 ºC	IR	5 100	µA
Typical Junction Capacitance Note1	Cj	25	pF
Operating and Storage Temperature Range	Tj, Tstg	-55 ~ +150	ºC
Note: 1. Measured at 1MHz and applied reverse voltage of 4 VDC.			

RATINGS AND CHARACTERISTICS CURVES (TA = 25 °C unless otherwise noted)

Fig.1 Current Derating, Case




Fig.2 Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 Typical Forward Voltage







Fig.4 Typical Reverse Characteristics




PACKAGE OUTLINE DIMENSIONS



GBU		
Dim	Min	Max
A	21.70	22.50
B	3.40	4.10
C	7.40	8.00
D	1.65	2.26
E	2.25	2.85
F	2.05	2.4
G	1.02	1.37
H	4.83	5.43
J	17.0	18.6
L	18.3	18.9
M	3.30	3.66
N	0.46	0.66




Marking Information



①W : Company's trademark


②Product model : GBU806L

③PDC information:




Packaging Information

1.Inside Box



2.Outside Box



Packaging Information

NO	UNIT	Inside Box			Outside Box		
Size	mm	L1	W1	H1	L2	W2	H2
		228	110	43	460	240	235
QTY	PCS	250PCS/carton			5,000PCS/carton,20boxes in total		
Note	Tolerance ≤20mm,±3mm; 21-100mm,±5mm; 101-500mm,±10mm						